

Product Brochure For B014

Metal Cutting Band Saw - Swivel Vice - BS-912

Mitre Cuts Up To 45°, Quick Action Material Clamp & Includes Hydraulic Down Feed Control

On Sale

Ex GST	Inc GST
\$2,746.00	\$3,157.90
\$2,373.91	\$2,730.00



ORDER CODE:	B014
MODEL:	BS-912
Operation Type:	Fixed Head
Round @ 90° (mm):	230
Round @ 45° (mm):	150
Round @ 60° (mm):	~
Square @ 90° (mm):	230
Square @ 45° (mm):	127
Square @ 60° (mm):	~
Rectangle (W x H) @ 90° (mm):	305 x 178
Rectangle (W x H) @ 45° (mm):	150 x 127
Rectangle (W x H) @ 60° (mm):	~
Coolant System:	Yes
Table Working Height (mm):	640
Cutting Head Beam Type:	Manual
Cutting Head Beam Return:	Manual Return
Cutting Head Down Feed Control:	Adjustable Hydraulic
Vice Clamping Fixture:	Manual
Bundle Cutting Fixture:	~
Blade Steps / Speeds (M/Min):	26-50-73-96
Blade Size (L x W x T) (mm):	2654 x 27 x 0.9
Motor Power (kW / hp):	0.75 / 1
Voltage / Amperage (V / amp):	240 / 10
Nett Weight (kg):	185



Description

Manufactured in Taiwan

The BS-912 is a larger 240 volt band saw suitable for the medium fabrication and general engineering workshops. It features increased motor power, four blade speeds, double row ball bearing blade guides, a built-in coolant system and greatly increased cutting capacity.


The downward cutting pressure is controlled by a fully adjustable hydraulic damper with an on/off valve and there is an automatic cut-off at the end of the cut. The vice rotates for mitre cutting and there is an adjustable material stop for consistent repeat length cutting.

Features

- 305 x 178mm (W x H) rectangular capacity
- Adjustable hydraulic feed cutting rate for multiple applications
- Mitre cuts to 45° using calibrated vice
- Built-in coolant system to both blade guides for maximum cutting efficiency
- Limit switch stops machine when cut is complete
- Quick action material clamping lever
- Adjustable blade roller guides provides accurate cutting
- Adjustable 4-speed pulley drive system enabling 26-50-73-96mpm cutting speeds
- Adjustable length stop for repetition cutting
- Wire wheel brush to clean swarf from blade
- Portable - on wheels for ease of use
- Automatic electric cut-out switch
- Heavy-duty 750W 240V fully enclosed fan-cooled motor

Product Brochure For B014

Specific Features




Bearing Blade Guide




Hydraulic Ram Down Feed Control



Hydraulic Ram



Length Stop



Speed Selection Chart		912 8/DR 132050
Driven Pulley	Motor Pulley	Speed F.P.M/M.P.M
		60Hz 50Hz
		105(32) 85(26)
		196(60) 164(50)
		288(88) 240(73)
		377(115) 312(95)

Speed Chart



Coolant System



Blade Guide Wire Brush



Bearing Blade Guide



Guide Adjustment

Product Brochure For B014

Recommended Accessories

B220

Metal Band Saw Blade - 6TPI
Carbon, Blade - 2654 x 25.4 x
0.90mm



B223

Metal Band Saw Blade - 10TPI
Carbon, Blade - 2654 x 25.4 x
0.90mm



B226

Metal Band Saw Blade - 14TPI
Carbon, Blade - 2654 x 25.4 x
0.90mm



B412

Metal Band Saw Blade - 4-6TPI
Bi-Metal, Blade - 2654 x 25.4 x
0.90mm



B414

Metal Band Saw Blade -
6-10TPI Bi-Metal, Blade - 2654 x
25.4 x 0.90mm



B418

Metal Band Saw Blade -
10-14TPI Bi-Metal, Blade - 2654
x 25.4 x 0.90mm



S091

Soluble Metal Cutting Fluid - 20
Litre



S090A

Soluble Metal Cutting Fluid - 1
Litre



Product Brochure For B014

S090

Soluble Metal Cutting Fluid - 5 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S074

Cutting Tool Lubricant Paste - 500g



L300

Magnetic Swarf Remover



M9991

Magnetic Floor Sweeper



L812

Roller Conveyor



L816

Roller Conveyor Stand



W343A

Roller Stand



W343

Roller Stand



W3434

Roller Stand



W3436

Roller Stand - V-Type




Product Brochure For B014

M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



O043
Rust & Corrosion Preventive



O042
General Purpose Lubricant & Corrosion Inhibitor



O044
Rust & Corrosion Preventive

