

## Product Brochure For L179G

### Centre Lathe - AL-340G

356 x 500mm Turning Capacity - 39mm Bore

Includes Digital Readout System & Quick Change Toolpost



ORDER CODE:	L179G
MODEL:	AL-340D
Swing Over Bed (mm):	356
Distance Between Centres (mm):	500
Spindle Bore (mm):	39
Swing In Gap (mm):	515
Swing Over Cross-slide (mm):	220
Digital Readout System Fitted:	Yes
Quick Change Toolpost Fitted:	Yes
Leadscrew Covers Fitted:	Yes
Taper Turning Attachment:	~
Coolant System:	Yes
Tool Height To Suit (mm):	16
Centre Height (mm):	178
Spindle Nose Size or Type:	D1-4 Camlock
Bed Width (mm):	187
Headstock Spindle Taper (MT):	5
Tailstock Taper (MT):	3
Cross Slide Travel (mm):	160
Compound Slide Travel (mm):	68
Leadscrew Type:	Metric
Metric Cross Feed (X-Axis) (mm/rev):	0.018 - 0.583
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	0.082 - 2.711
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	32 (0.4 - 7.0)
Imperial Thread Steps & TPI (No. / TPI):	32 (4 - 56)
3 Jaw Chuck Diameter (mm):	160
4 Jaw Chuck Diameter (mm):	200
Spindle Steps / Speeds (No. / rpm):	16 (35 - 2000)
Motor Power (kW / hp):	1.5 / 2
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	595

### Features

- 2 Axis digital readout system
- Quick change toolpost with 4 holders
- Concertina leadscrew cover
- Gear drive headstock for quick change of spindle speeds
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Low voltage work light
- Foot operated spindle brake with safety cut out switch
- Change gears for metric and imperial thread cutting
- Oil sight glass for head stock and gearbox
- Adjustable taper roller bearings support the spindle
- Micro-adjustable length-stop on bed-way for accurate repetitive operation
- 2HP/415V motor 16-speed (35-2000rpm)
- Inching button is incorporated on the control panel for convenient spindle speed selection
- Enclosed quick action gearbox for thread cutting and auto feeding
- Powered longitudinal and cross feeds
- D1-4 camlock spindle for quick chuck changes and safe reverse direction turning. ISO standard
- Removable gap bed-way for larger diameter jobs
- Dual calibrated dials (except for saddle handwheel)
- Chuck & change gear guards are fitted with micro switches
- Coolant system with flexible hose
- Slide out swarf tray

Product Brochure For L179G

**Includes**

- 2 Axis digital readout system
- Concertina leadscrew cover
- Quick change tool post with 4 holders
- 3-jaw chuck with reverse jaws
- 4-jaw chuck
- Face plate
- Fixed steady
- Travelling steady
- Change gears
- Dead centres
- Thread-chasing dial
- Safety chuck guard
- Work light
- Stand
- Foot brake
- Rear splash guard & swarf tray
- Tool box
- Instruction booklet

**Specific Features**



2 Axis Digital Readout System



Chuck Guard with Micro Switch



Headstock




Headstock Controls 2



Spindle Speed Selection Levers



Feed Gearbox



Feed Gearbox



2 Speed Switch




Dial Chasing Gauge



Saddle Stop




Indicator Table




Leadscrew Covers


Product Brochure For L179G




Leadscrew Covers



Compound Slide



Quick Change Toolpost



Saddle Controls



Forward Reverse Engage Lever



Worklight and Coolant Nozzle



Foot Brake



Slide Out Drip and Swarf Tray

**Recommended Accessories**

G660

Lathe Leadscrew Cover Kit

G659

Lathe Leadscrew Cover Kit - Concertina

L0077

Lathe Turning Tool Kit - 7 piece Insert Type

L0078

Carbide Inserts - General Purpose



Product Brochure For L179G

**L451**  
Lathe Turning Tool Kit - 3 piece  
Insert Type



**L465**  
Professional Lathe Parting Tool  
Kit - Insert Type




**L457**  
Lathe Threading Tool Kit - Insert  
Type




**C052**  
3MT Live Centre




**L341**  
Fitting and Machining Technical  
Book



**L345**  
Handy Workshop Tips &  
Techniques - 1st Edition



**L3455**  
Professional Sheet Metal  
Fabrication Book



**L076**  
Knurling Tool Holder Kit



**C290**  
Heavy Duty Drill Chuck - Keyed  
Type



**D443A**  
3MT x JT3 Drill Chuck Arbor



**D1272**  
Metric 135° Precision HSS Drill  
Set - 25 Piece



**D1282**  
Imperial 135° Precision HSS  
Drill Set - 29 Piece



Product Brochure For L179G

**D126**  
Metric 135° Precision HSS Drill Set - 170 Pieces



**C980**  
5C Collet Lathe Adaptor




**L277**  
Vertical Mill Slide



**M800**  
Rubber Mat - Anti-Fatigue



**M805**  
Rubber Mat - Anti-Fatigue



**S090A**  
Soluble Metal Cutting Fluid - 1 Litre



**S090**  
Soluble Metal Cutting Fluid - 5 Litre



**S076**  
Cutting Tool Lubricant Fluid - 500ml



**S077**  
Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



**S074**  
Cutting Tool Lubricant Paste - 500g



**O043**  
Rust & Corrosion Preventive



**O042**  
General Purpose Lubricant & Corrosion Inhibitor



## Product Brochure For L179G

---

O044

Rust & Corrosion Preventive

