

Product Brochure For M586D

Industrial Turret Milling Machine - Horizontal & Vertical - BM-GEVS250

Table Travel: (X) - 700mm (Y) - 250mm (Z) - 440mm

Includes DRO & Pneumatic Drawbar System



On Sale

Ex GST

Inc GST

\$40,810.00

\$46,931.50

\$40,000.00

\$46,000.00

ORDER CODE:	M586D
MODEL:	BM-GEVS250
Digital Readout:	3-Axis Digital Readout
Type:	Vertical & Horizontal
Table Size (mm):	1100 x 250
Column Type:	~
Spindle Taper - Vertical:	NT40
Spindle Taper - Horizontal:	NT40
Longitudinal Travel (X-Axis) (mm):	700
Cross Travel (Y-Axis) (mm):	250
Vertical Travel (Z-Axis) (mm):	440
Type of Slides:	Dovetail (X, Y & Z)
Ram Travel (mm):	300
Spindle to Table (mm):	470
Spindle to Base:	~
Spindle Travel / Diameter (mm):	127 / 105
Throat Depth (max.) (mm):	500
Tilting Head (Left ~ Right):	±90°
Tilting Head (Forward ~ Back):	~
Drilling Capacity (mm):	~
End Milling Capacity (mm):	~
Face Milling Capacity (mm):	~
Power Feed - Quill (mm/rev):	0.037 / 0.076 / 0.152
Power Feed - Longitudinal (X-Axis) (mm/min):	0.02 - 0.20
Power Feed - Cross (Y-Axis) (mm/min):	Optional
Power Feed - Vertical (Z-Axis) (mm/min):	Rapid
Table T-Slot Size (inch / mm):	5/8
Work Table Load Capacity (kg):	300
Spindle Speeds Vertical (No./ rpm):	Variable (60 - 3600)
Spindle Speeds Horizontal (No./ rpm):	6 (40 - 980)
Spindle Speeds - Universal Head:	~
Motor Power - Vertical Spindle (kW / hp):	3.75 / 5
Motor Power - Horizontal Spindle (kW / hp):	2.25 / 3
Motor Power - Universal Head:	~
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	1350

Features

- Vertical spindle, Yaskawa inverter variable speed drive 60 – 3600rpm
- Horizontal spindle, 40-980 rpm speeds controlled by gear selection levers with oil bath lubrication
- 5HP vertical & 3HP horizontal spindle motors provide exceptional machining power
- NT40 spindle taper with Ø105mm chrome hardened and ground quill
- 1100 x 250mm hardened and ground worktable with ±45° left and right swivel
- Automatic quill feed 0.037, 0.076, 0.152mm/rev
- Vertical mill head swivels ±45° to left and right
- Spindle guard with micro switch
- 3-Axis digital readout fitted
- Pneumatic draw bar system for quick and effortless tool change
- Heavy duty gear driven X Axis power-feed
- Z-Axis powered elevating motor

Product Brochure For M586D

- Metric dial graduations @ 0.02mm for X , Y & Z-Axis
- Meehanite castings for superior rigidity
- Hardened and ground dovetail guideways
- Turcite-B coating on X & Y-Axis ways for wear resistance and smooth operation
- Auto lubrication system maintains proper lubrication to all slideways


Includes

- 3-Axis Digital Readout Fitted
- Automatic Lubrication System
- LED Lamp
- Coolant System
- Slide-way Covers
- Safety Cutter Guard
- Swarf Tray
- 1" Horizontal Arbor
- 2 x Horizontal Arbor Supports
- 2 x M16 Drawbars

Specific Features



Horizontal Head Setup



Horizontal Head Setup Close Up



Swivel Arm Control Panel



3 Axis Digital Read Out



Control Panel



Gear Drive Table Feed



Horizontal Speed Selection Levers



Spindle Controls



Swivel Table



Tilting Mill Head Left & Right to 90 Degrees



Rotating Horizontal Ram



Z Axis Feed Handle with Micro


Product Brochure For M586D



Z Axis Rapid Motor



Automatic Slideway Lubrication System



Y Axis Table Locks



Oil Feeder Distribution Block




Y Axis Feed Handle




X Axis Feed Handle



Air Powered Draw Bar System



Horizontal Spindle



Quill Feed Depth Stop



Variable Inverter Speed




Air Powered Draw Bar Control



Mill Head Right Side View



Quill Feed Engagement Dial



3 Speed Quill Feed



Mill Head Left Side View



High Low Spindle Speed Gear Lever

Product Brochure For M586D



Includes Horizontal Arbor

Recommended Accessories

M184
Precision Boring Head



M197A
Boring Head Shank



C290
Heavy Duty Drill Chuck - Keyed Type



C292
Industrial Drill Chuck - Keyless Type



C294
Industrial Drill Chuck - Keyless Type



D446
NT40 x JT6 Drill Chuck Arbor - M16 Threaded Shank



D448
NT40 x JT3 Drill Chuck Arbor - M16 Threaded Shank



M3301
Metric HSS Slot Drill & End Mill Set - 10 Piece



Product Brochure For M586D

M3321
Imperial HSS Slot Drill & End Mill Set - 10 Piece



C966
Collet & Chuck Set - 25 Piece




V105
Vertex K-Type Milling Vice




V106
Vertex K-Type Milling Vice



V305
Vertex Anglock Machine Vice



V306
Vertex Anglock Machine Vice



R008
Vertex Rotary Table



R010
Vertex Rotary Table



D001
Vertex Dividing Head - Semi Universal



D002
Vertex Dividing Head - Semi Universal



R002
Vertex Super Indexing Head



C280
3 Jaw Self Centring Lathe Chuck



Product Brochure For M586D

C2806
3 Jaw Self Centring Lathe Chuck



M247
Air Power Drawbar



M2295
Power Feed Unit



M229
Power Feed Unit



L065
KYOCERA Carbide Inserts - Milling



M510
Face Mill 90° - Positive Rake



M512
Face Mill 90° - Positive Rake



M503
Face Mill 90° - Positive Rake



M515
Face Mill 45° - Super High-Rake



M517
Face Mill 45° - Super High-Rake



M518
Face Mill 45° - Super High-Rake



M550
Face Mill Arbor



Product Brochure For M586D

M552
Face Mill Arbor




M554
Face Mill Arbor



M555
Face Mill Arbor



L066
KYOCERA Carbide Inserts - Milling



M252
Parallel Set - 18 Piece



M250
Parallel Set - 8 Piece



M519
End Mill - Ø12mm



M520
End Mill - Ø16mm



M521
End Mill - Ø20mm




L059
Carbide Inserts - Milling



M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



Product Brochure For M586D

S090A

Soluble Metal Cutting Fluid - 1 Litre



S090

Soluble Metal Cutting Fluid - 5 Litre



S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S074

Cutting Tool Lubricant Paste - 500g



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant & Corrosion Inhibitor



O044

Rust & Corrosion Preventive

