

Product Brochure For R802

Professional Electronic Variable Speed Lathe - CL4-CAM

Ø305mm Swing x 914mm Between Centres

Shown with Optional
CL3/B Bowl Turning
Attachment &
RPLB24-48 Lathe Stand



ORDER CODE:	R802
MODEL:	CL4-CAM
Swing Over Bed (mm):	305
Between Centres (mm):	914
Spindle Nose Thread:	3/4" x 16TPI
Spindle Nose Taper (MT):	1
Spindle Speeds (rpm):	Variable 13 - 4600
Tailstock Taper (MT):	1
Motor Power (kW / hp):	0.75 / 1
Voltage / Amperage (V / amp):	240 / 10
Floor Space (W x D x H) (mm):	1560 x 530 x 510
Floor Space With Option Stand (W x D x H) (mm):	1560 x 650 x 1140
Nett Weight (kg):	100

RECORD POWER



Description

Record Power CL4-CAM Professional Electronic Variable Speed Lathe

Most serious and professional woodturners have realised the benefits of infinitely variable speed control. This allows the user to run the lathe at just the right speed for the job, with a simple turn of a dial. The speed can be varied from 13 to 4600 rpm*. Newly upgraded, the electronics and inverter are now housed in a dust proof metal enclosure certified to IP55 standard. This offers even greater levels of protection for the advanced control circuits. This speed control unit should not be confused with cheap and inferior expanding pulley systems, which have limited speed ranges, often have vibration problems and due to the inherent weakness in their design, wear belts at a rapid rate. The Record Power CL4 uses a 3 phase motor and inverter to provide the power and is a truly professional solution, used throughout the machine tool industry.

*Most turning can be achieved safely and effectively between 400 and 2000rpm. The higher speeds are only to be used by experienced turners who have had adequate training and observe all recommended safety and operating procedures.

Features

- Headstock - The headstock is now made from cast steel for extra strength. The phosphor bronze bearing offers long life, unrivalled support and is adjustable to offer years of reliable performance.
- Capacity - 12" bowl capacity over bed, 30" with headstock swivelled.
- Massive Capacity - With a 36" capacity between centres and the ability to turn up to a 30" bowl when using the optional CL3/B all your turning needs can be catered for.
- Bed Bars - The solid steel chromed bed bars add weight, rigidity and strength while providing smooth travel for head, tail and toolrest banjo.
- Tailstock - Heavy duty tailstock within a cast iron construction gives stability and support to the workpiece. It is hollow to enable easy ejection of centres and allow for long hole boring and also features easy to use cam locks.
- Cam Action Banjo and Tailstock - Strong cast banjo and tailstock for easy one-handed repositioning.
- Variable Speed Unit - Recently improved and now more efficient. Provides simple, responsive and smooth speed change at the turn of a dial. This unit is assembled in the UK using components from a high quality German supplier. It is the industrial solution to variable speed control.

Includes

- Drive centre
- Dead centre

Optional Accessories

- CLO/H 17" Tool Rest
- CLO/J 10" Tool Rest
- CL3/B Bowl Turning Attachment

Product Brochure For R802

- RPLB24-48 Adjustable Lathe Stand
- CLO/C Cam Lock Tool Rest Upgrade

Specific Features



Phosphor Bronze Bearing



Cast Iron Headstock



Headstock




Variable Speed Unit



Tailstock



Large Bowl



Action

Recommended Accessories

W300

Carbide Wood Turning Tools - 6 Piece Set



W301

HSS Wood Turning Tools - 8 Piece Set



W302

HSS Wood Turning Tools - 6 Piece Set



W305

Bowl Sanding Tool



Product Brochure For R802

W370
Scroll Chuck -100mm



W367
Scroll Chuck Insert - 3/4" x
16TPI



W375
Scroll Chuck Accessory Kit

