

## Product Brochure For S902GL

### Hydraulic NC Pressbrake - PB-70B

70T x 3200mm - Includes Laser Safety Guarding  
Estun NC-E21 Control 2-Axis with Ballscrew Backgauge

**On Sale**

Ex GST

Inc GST

**\$40,566.00**

**\$46,650.90**

**\$38,600.00**

**\$44,390.00**



ORDER CODE:	S902GL
MODEL:	PB-70B
Control Unit (Type):	Estun NC-E21
Nominal Pressure - Tonnage (Ton):	70
Nominal Pressure - Kilonewtons (kN):	630
Length of Work Table (mm):	3200
Distance Between Columns (mm):	2650
Throat Depth (mm):	250
Maximum Open Height (mm):	360
Ram Stroke (mm):	100
Machine Axis (No.):	2
Safety Guarding System (Type):	Laser System
Backgauge Travel (mm):	520
Table Bed Crowning System (Type):	~
Motor Power (kW / hp):	5.5 / 7.5
Motor Voltage (V):	415
Floor Space Requirements (L x W x H) (mm):	~
Nett Weight (kg):	5740

METALMASTER



#### Description

MetalMaster Quality Pressbrakes feature high durability, and provide precision bending capabilities. The Pressbrake main frames are constructed from rolled, stress relieved solid steel to prevent distortion during the bending process and under extreme continuous loads.

MetalMaster Pressbrakes are produced in a high volume production process and therefore are able to be manufactured cost effectively, resulting in an affordable price, representing value for money and quicker return on investment.

All electrical components are of European quality supplied by, Telemecanique, Merlin Gerin and ABB.

#### Features

- ESTUN E21 NC Controller
- Stores up to 40 programs with 25 bending steps per program
- Position control of Backgauge
- Backgauge retract function
- Bottom stroke dwell timer
- Work piece counting
- One-key backup / restore
- LCD Display
- LASER GUARDING -
- Laser guarding provides close proximity operator protection allowing faster bending cycles, promoting higher productivity
- The Laser system is compliant with requirements of EN61496-1, EN61496-2, ISO 13849-1 Ple, as well as AS/NZS 4024.1503
- Australian designed electrical system featuring dual channel monitoring on all essential machine functions
- Top beam speed & stopping performance are all real time monitored to ensure compliance with safety regulations
- METALMASTER Pressbrakes -
- Dual Hydraulic rams balanced by a heavy duty torsion bar, Electronically controlled by the E21 NC control assuring accuracy & repeatability.
- High performance side mount back gauge with linear guides & ballscrew provides fast and accurate positioning
- Segmented heavy duty 35° top punch
- European style punch holder with an adjustable wedge clamping system for crowning
- Multi vee ('V') bottom die is made from one solid 3200mm die block design to handle heavy plate, safety edge vee ('V') is incorporated in bottom die block.
- Sliding steel fabricated sheet supports enabling a wide range of material sizes to be aligned and supported at the correct required height.

## Product Brochure For S902GL

---

This feature is achieved with a "T" slot machined down the total length of the die bed, sheet supports are also adjustable vertically to assist in supporting material with return bends already folded.

- Metal safety guarding surrounding the machine with rear sliding door fitted with micro switch ensuring operator safety.
  - Hydraulic pressure gauge with quick adjust pressure control & over pressure protection allows the operator to accurately set the pressure required for different material thickness.
  - The vertical supporting slides are treated to provide greater wear resistance and increased accuracy.
  - Reinforced side frames providing addition support strength to machine throat
  - Includes laser guarding system
  - Mild steel capacity is rated on hot rolled material with 250MPA
- 
- Pre-Commissioning:
    1. Pressbrake is run & tested prior delivery
    2. Hydraulic oil is included with machine

### **Includes**

- ESTUN NC- E21 control mounted on a swivel pendant for optimal ergonomics
- LED superior bright work lights provides clearer view to workpiece
- Sliding front sheet support arms
- Mobile dual operation foot control
- Segmented 35° offset top tooling (3x800, 1x365, 1x200, 1x100, 1x50, 1x40, 1x20, 1x15, 1x10)
- Multi V bottom die block 75 x 75mm with a range of V's between 4mm~40mm
- Top tooling tool intermediate holder system with wedge type adjustment
- Premium linear way side mount ballscrew backgauge with 520mm travel
- Metal constructed safety guarding surrounding machine

## **GL Model: Laser guarding safety**

- 1. Laser guarding provides close proximity protection allowing faster bending cycles higher productivity.**
- 2. The Laser system is compliant with requirements EN61496-1, EN61496-2, ISO 13849-1 PL3 AS/NZS 4024.1503**
- 3. Australian designed electrical system for channel monitoring on all essential machines**
- 4. Top beam speed & stopping performance monitored to ensure compliance with safety standards**

Product Brochure For S902GL

**Specific Features**



Enclosed Rear Safety Guarding



NC Estun E21 Controller




NC Estun E21



Left Laser



Right Laser




Laser Alignment Guide




Adjustable Travel Limit Control



Laser Guarding system In Use



LM Guide Ballscrew Backgauge



LM Guide Ballscrew Backgauge




Adjustable Sliding Front Sheet Supports




Intermediate Clamps




Adjustable Top Tool Taper Wedge System



Top and Bottom Tooling



Segmented Top Punch



One Piece 4 Sided Die

Product Brochure For S902GL



Mobile Foot Control




Mobile Foot Control Top Buttons



Heavy duty Torsion Bar



Adjustable Pressure Control



Tonnage Calculation Chart

**Recommended Accessories**

**S988**

Quick Action Intermediate Clamps



**S990S**

35° Top Punch Pressbrake Tooling - Segmented



**S990**

35° Top Punch Pressbrake Tooling




**S990F**

35° Top Punch Pressbrake Tooling



Product Brochure For S902GL

**S9927**  
75mm Die Block Pressbrake Tooling



**S991**  
86° Top Punch Pressbrake Tooling




**S991S**  
86° Top Punch Pressbrake Tooling - Segmented



**S9920**  
86° Top Punch Gooseneck Pressbrake Tooling




**S9920S**  
86° Top Punch Gooseneck Pressbrake Tooling - Segmented



**S996**  
15° Top Punch Pressbrake Tooling



**S996A**  
60mm Die Block Pressbrake Tooling



**S996B**  
60mm Die Rail Pressbrake Tooling



**Q200**  
Combination Set



**Q200A**  
Combination Set



**Q201**  
Universal Bevel Protractor



**Q2105**  
Digital Height Gauge



Product Brochure For S902GL

**M970**  
Digital Angle Rule

**M972**  
Digital Angle Rule

**M974**  
Digital Angle Rule

**M800**  
Rubber Mat - Anti-Fatigue



**M805**  
Rubber Mat - Anti-Fatigue

**O043**  
Rust & Corrosion Preventive

**O042**  
General Purpose Lubricant &  
Corrosion Inhibitor

**O044**  
Rust & Corrosion Preventive

