

## Product Brochure For S923

### Hydraulic NC Guillotine - HG-460B

1300 x 6mm Mild Steel Shearing Capacity

1-Axis Ezy-Set NC-89 Controlled Backgauge & Includes Rapid Blade Adjustment

**On Sale**

Ex GST

Inc GST

**\$18,606.00**

**\$21,396.90**

**\$14,200.00**

**\$16,330.00**



ORDER CODE:	S923
MODEL:	HG-460B
Shearing Capacity - Mild Steel (mm):	6
Shearing Capacity - Stainless Steel (mm):	4
Shearing Length (mm):	1300
NC Control (Type):	Ezy-Set NC-89
Backgauge (Type):	Leadscrew
Backgauge Travel (mm):	700
Pneumatic Sheet Supports:	~
Quick Action Blade Clearance Adjustment:	Yes
Strokes / min (SPM):	12
Blade Angle (deg):	2°
Throat Depth (mm):	~
Motor Power (kW / hp):	5.5 / 7.5
Voltage / Amperage (V / amp):	415
Floor Space Requirements (L x W x H) (mm):	1990 x 2230 x 1312
Nett Weight (kg):	2046

METALMASTER



#### Features

- 1300mm x 6mm cutting capacity
  - 5.5kW / 7.5hp 415V motor
  - Ezy-Set NC-89 Go-To digital display controlled backgauge with DRO counter
  - Quick action blade clearance adjustment for shearing material 1 - 6mm
  - Hydraulic material clamping for accurate shearing
  - One shot lubrication pump & reservoir for slideway protection
  - Blades made from 9CrSi material suitable for cutting stainless steel
  - Transfer balls inserted into work table allowing larger sheets to be easily positioned to the cut position and squaring arm
  - Front sheet supports with ball bearing guides preventing material damage when setting up
  - Three safety photo electric light beams on rear guarding
  - Safety reset rear guarding button mounted to back of electrical box
  - Heavy duty under driven machine construction
  - Equipped with shadow line lighting-alignment device
  - Roving foot pedal control
  - Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
    1. Guillotine is run & tested prior delivery
    2. Hydraulic oil is included with machine

Product Brochure For S923

**Specific Features**



Right View



Rear View



NC 89 Control Panel



NC 89 Backgauge DRO



Squaring Arm with Measuring Scale



Material Transfer Balls On The Table



Front Sheet Supports with Roller Bearings




3 Safety Photo Sensors



Quick Action Blade Clearance Adjustment



One Shot Lubrication




Roving Foot Pedal with Emergency Stop

Product Brochure For S923

**Recommended Accessories**

S9981

1320mm Sheet Metal Guillotine  
Blade Set - 9CrSi




M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



O043

Rust & Corrosion Preventive



O042

General Purpose Lubricant &  
Corrosion Inhibitor



O044

Rust & Corrosion Preventive

